



---

## Technical Instruction

---

### Transparent waterproof glue

---

Transparent waterproof glue is suitable for waterproof repair of outdoor wall leakage of various buildings; Suitable for waterproof and moisture-proof of interior and exterior wall decoration materials;

Transparent waterproof glue can produce a variety of single-component waterproof coating, water-based industrial paint, etc., can be applied to wood, and a variety of basic cover surface ultra high gloss, salt spray resistance, good water resistance, bubble water is not white, good weather resistance, yellow resistance, strong adhesion, high transparency after film formation, non-stick ash.

---

### Technical data

---

Project	Unit	Value
Appearance	/	Milky white translucent liquid
Solid content	%	30±1
viscosity	(23±2℃) mPa.s	≥5000
PH	GB/T 27573	7~9
GTT	℃	25
MFFT	℃	12

---

## Product Application

---

Transparent waterproof glue can be used as an adhesive in the following areas :

- Waterproof repair of outdoor wall leakage
- Waterproof and moisture-proof surfaces of interior and exterior wall decoration materials
- Used in the production of various single component waterproof paint, waterborne industrial paint, etc
- Suitable for wood, and all kinds of base surface

---

## Storage

---

- Storage temperature ranged from 5 to 35°C .
- If the emulsion is not opened, it is necessary to seal the opening as soon as possible to avoid drying the surface.
- Transparent waterproof glue is unopened and stored under appropriate conditions for 6 months. After long-term storage, it is recommended to stir before use.

---

## Packaging of products (can be customized)

---

- tank car
- Container liquid bag
- IBC pallet tank
- 220 Kg iron barrel
- At 50Kg PE barrels

---

## Transport

---

Ensure that the packaging is complete and sealed during transportation to prevent microbial invasion and phenomena such as crust.